

file 347:JAPIO Oct 1976-1999/Apr.(UPDATED 990812)

(c) 1999 JPO & JAPIO

\*File 347: Display front page images using format 19. See HELP NEWS 347 for more information

Set Items Description

?s an=5-085609

S1 1 AN=5-085609

?

?t s1/7

1/7/1

DIALOG(R)File 347:JAPIO

(c) 1999 JPO & JAPIO. All rts. reserv.

04445181 \*\*Image available\*\*

LIQUID CRYSTAL FLAT PANEL DISPLAY DEVICE

PUB. NO.: 06-089081 [JP 6089081 A]

PUBLISHED: March 29, 1994 (19940329)

INVENTOR(s): TOOMASU ESU BUZATSUKU

APPLICANT(s): SONY TEKTRONIX CORP [417165] (A Japanese Company or Corporation), JP (Japan)

APPL. NO.: 05-085609 [\*JP 9385609\*]

FILED: March 19, 1993 (19930319)

PRIORITY: 7-854,145 [US 854145-1992], US (United States of America),  
March 19, 1992 (19920319)

#### ABSTRACT

PURPOSE: To provide an electrooptic address assigning device with decreased crosstalk effect by incorporating a liquid crystal material showing such frequency reactivity that the dielectric anisotropy for the signal frequency higher than the critical frequency is almost zero.

CONSTITUTION: The line electrode 20 is formed on the principal plane of a non-conductive light transmitting substrate 24, and a groove 22 is formed on the principal plane of the second nonconductive light transmitting substrate 26. A layer 28 consisting of a frequency-reactive electrooptical material such as two-frequency nematic liquid crystal is interposed between a first nonconductive light transmitting substrate 24 and a second nonconductive light transmitting substrate 26. In this constitution, it is preferable that the dielectric anisotropy  $\Delta\epsilon$  of the frequency-reactive liquid crystal material in the layer 28 is rather small for the signal frequencies higher than the specific frequency  $f_{th}$ , and more preferably, almost zero. Thereby, the frequency-reactive liquid crystal material does not substantially react with signals having higher frequencies than the critical frequency. This device includes a data driver which sends reversed data signal in a first period and non-reversed data signal in the second period to each picture element.

?

B75